

TCM 0325 Series Coriolis Mass Flow Meter

Advantages:

- > Robust for long life
- > Customized installation length
- > Excellent repeatability
- > Option for 345 bar (5000 psi)

Benefits:

- > Increased productivity
- > Considerable cost savings for installation
- > Increased product quality
- > Accurate chemical injection metering

Pressure Rating: 200 bar, 2900 psi

Specifications:

Mass Flow Rate (max.): 325 kg/h, 11 lb/min
 Volumetric Flow Rate (max.): 325 l/h, 1.31 gpm, 49 bbl/d
 Nominal Meter Size: DN4, 1/8"

Accuracy [liquids]:¹

Basic Accuracy [Mass Flow]: $\pm 0.1\%$ of flow rate
 Mass Flow Repeatability: $\pm 0.05\%$ of flow rate
 Basic Accuracy [Volume Flow]: $\pm 0.15\%$ of flow rate
 Volume Flow Repeatability: $\pm 0.05\%$ of flow rate
 Zero Stability: $\pm 0.01\%$ of full scale

Accuracy [gases]:

Basic Accuracy [Mass Flow]: $\pm 0.5\%$ of flow rate
 Mass Flow Repeatability: $\pm 0.25\%$ of flow rate

Density:


Density Range: up to 2500 kg/m³, 2.5 g/cm³
 Density Accuracy: Liquids ± 1.0 kg/m³, ± 0.001 g/cm³
 Density Repeatability: ± 0.5 kg/m³, ± 0.0005 g/cm³

Temperature:


Process Temperature Range: standard:
 -40 °C ... +100 °C, -40 °F ... +212 °F
 optional:
 -60 °C ... +200 °C, -76 °F ... +392 °F
 Temperature Accuracy: ± 1 °C $\pm 0.5\%$ of reading
 ± 1.8 °F $\pm 0.5\%$ of reading
 Temperature Repeatability: ± 0.2 °C, ± 0.36 °F

Materials of Construction [wetted parts]:

Tubes: 1.4404 / AISI 316L
 Case: 1.4301 / AISI 304 (1.4404 / AISI 316L)
 Flow Splitter: 1.4404 / AISI 316L
 Brazing Alloy: BNi-2




Meter Dimensions:¹



Compact Version

weight: 7 kg/15.5 lb
with meter mount ex-electronics
meter connection: G1/2" thread



Remote Version

weight: 8.3 kg/18.3 lb
with junction box & remote field mount
meter connection:
standard meter connection according table

Electronics:

The TCE-8000 transmitter offered with the TRICOR Coriolis Mass Flow Meter is also available with other mounting options.

Ex Certifications:

ATEX	Zone 1: Group IIC, T4 Zone 2: II 3G Ex nA IIC, T4 Gc
IECEX	Zone 1: Group IIC, T4
cCSAus Ex	Class I, Division 1: Group A, B, C, D, T4

Panel Mount²



Remote Field Mount³



Power Supply: 24 V DC $\pm 20\%$ or 90 ... 264 V AC
Outputs: Analog, Frequency, Pulse, Status
Interface: RS485 RTU (Modbus), HART®
More options on request

¹ Drawing of the Meter Dimensions reflects one standard connection, other connections on request.
(Installation length can vary depending on selected connection)

² weight: 0.4 kg/0.88 lb

³ weight: 3.8 kg/8.3 lb with 3 m cable